

1270 R.AXWD12.WS12

DIMENSIONS 640 x 480 mm

ADEQUATE HEIGHT, ERGONOMICS 1015 mm (work surface – floor).

WORK SURFACE

- Polyethylene, PE. Asepsis, hygiene, easy-to-clean.
- Withstands alcohol, detergents, disinfectants, chlorhexidine.
- Protection on all 4 sides. Pleasant to the touch, rounded shapes.

MONOBLOC STRUCTURE

- Stainless steel AISI-304. Assembly with rivets and TIG welding.

ISO DRAWER FRAMEWORK

- Total opening.
- Steel ball-bearing slides with self-closing system.
- Front stop, it protects the slide against strong impacts when closing.
- Load capacity per drawer: 20 kg.
- Interior frame ISO 600 x 400 mm.
- Polyethylene drawer front part, thickness 10 mm, 6 colours (Ref. G, Y, W, B, F, R).
- Ergonomic handle.
- Card holder with white cards, removable.

ISO DRAWERS 600 x 400 mm

- Heights 50, 100, 200 mm. Interchangeable, ABS.
- ISO norm 3394.

EXTENSIVE MOBILITY TROLLEYS

- Elevated push handle. Ergonomics, height 1055 mm.
- Simple wheels Ø 125 mm, 2 antistatic, 2 with brake.



1270 R.AXWD12.WS12
165 R.AXWD12.WS12.12.14.28.36.40

ACCESSORIES

- AXWD12: REMOVE Ø 125 mm DOUBLE WHEELS
- WS12: Ø 125 mm SIMPLE WHEELS
- 12: MANUAL LOCKING
- 14: NUMBERED DISPOSABLES SEALS 100 units
- 28: ROTATING ARM
- 36: GAS BOTTLE STAND
- 40: SERUM HOLDER