

3105LW G

DIMENSIONS 640 x 480 mm

HEIGHT 855 mm (work surface – floor).

WORK SURFACE

- Polyethylene, PE. Asepsis, hygiene, easy-to-clean.
- Withstands alcohol, detergents, disinfectants, chlorhexidine.
- Protection on all 4 sides. Pleasant to the touch, rounded shapes.
- Raised sides make it possible to move the trolley without needing the push handle.

MONOBLOC STRUCTURE

- Stainless steel AISI-304. Assembly with rivets and TIG welding.

ISO DRAWER FRAMEWORK

- Total opening.
- Steel ball-bearing slides with self-closing system.
- Front stop, it protects the slide against strong impacts when closing.
- Load capacity per drawer: 20 kg.
- Interior frame ISO 600 x 400 mm.
- Polyethylene drawer front part, thickness 10 mm, 6 colours (Ref. G, Y, W, B, F, R).
- Ergonomic handle.
- Card holder with white cards, removable.

ISO DRAWERS 600 x 400 mm

- Heights 50, 100, 200 mm. Interchangeable, ABS.
- ISO norm 3394.

STATIC TROLLEYS

- Without push handle - Easy left panel cleaning.
 - Free left side for mounting accessories.
- Double wheels Ø 100 mm, 2 antistatic, 2 with brake.



3105LW G
362M5LW G.26(RA4.A5).32R

ACCESSORIES

- 26(RA4.A5): BINS DISPENSERS
- 32R: SIDE SUPPORT