



606 DN.(2)60.(4)72.73

DIMENSIONS 640 x 480 mm

HEIGHT 1655 mm

MONOBLOC STRUCTURE

- Stainless steel AISI-304. Assembly with rivets and TIG welding.

ISO PANELS

- Flexible organisation inside the trolley.
- Adjustable shelves, phenolic, for bulky material.

ISO DRAWERS 600 x 400 mm

- Heights 50, 100, 200 mm. Interchangeable, ABS.
- ISO norm 3394.

2 DOORS

- Total opening 270°.
- 10 mm thickness.
- Lock with 4 keys.
- Card holder with white card, removable, left door.
- DN HPL phenolic light grey, TT Transparent methacrylate.

LOAD CAPACITY

- 150 kg.

VERTICAL HANDLES

- 2 left side, 2 right side.

EXTENSIVE MOBILITY TROLLEYS

- 4 wheel bumpers for hits.
- Wheels load capacity 400 kg.
- Ø 125 mm double wheels, 2 antistatic, 2 with dual lock.

Pedal position: Fixed wheel. Swivel wheel. Locked wheel.



606 DN.(2)60.(4)72.73

ACCESSORIES

- (2)60: ADJUSTABLE SHELVES
- (4)72: ISO DRAWERS 100 mm
- 73: ISO DRAWER 200 mm