

**606 DN.(8)72.73**

DIMENSIONS 640 x 480 mm

HEIGHT 1655 mm

**MONOBLOC STRUCTURE**

- Stainless steel AISI-304. Assembly with rivets and TIG welding.

**ISO PANELS**

- Flexible organisation inside the trolley.

**ISO DRAWERS 600 x 400 mm**

- Heights 50, 100, 200 mm. Interchangeable, ABS.
- ISO norm 3394.

**2 DOORS**

- Total opening 270°.
- 10 mm thickness.
- Lock with 4 keys.
- Card holder with white card, removable, left door.
- DN HPL phenolic light grey, TT Transparent methacrylate.

**LOAD CAPACITY**

- 150 kg.

**VERTICAL HANDLES**

- 2 left side, 2 right side.

**EXTENSIVE MOBILITY TROLLEYS**

- 4 wheel bumpers for hits.
  - Wheels load capacity 400 kg.
  - Ø 125 mm double wheels, 2 antistatic, 2 with dual lock.
- Pedal position: Fixed wheel. Swivel wheel. Locked wheel.

**606 DN.(8)72.73**  
**606 DN.(8)72.73****ACCESSORIES**

- (8)72: ISO DRAWERS 100 mm
- 73: ISO DRAWER 200 mm