

620 DN.(12)72.(4)73

DIMENSIONS 900 x 630 mm **HEIGHT** 1675 mm

MONOBLOC STRUCTURE

- Stainless steel AISI-304. Assembly with rivets and TIG welding.

ISO PANELS

- Flexible organisation inside the trolley.

ISO DRAWERS 400 x 600 mm

- Heights 50, 100, 200 mm. Interchangeable, ABS.
- ISO norm 3394.

2 DOORS

- Total opening 270°.
- 10 mm thickness.
- Lock with 4 keys.
- Card holder with white cards, removable, left door.
- DN HPL phenolic light grey, TT Transparent methacrylate.

LOAD CAPACITY

- 160 kg.

VERTICAL HANDLES

- 2 left side, 2 right side.

EXTENSIVE MOBILITY TROLLEYS

- 2 bumpers for hits of polyethylene, PE.
 - 4 wheel bumpers for hits.
 - Wheels load capacity 440 kg.
 - Ø 150 mm double wheels, 4 antistatic, 2 with dual lock.
- Pedal position: Fixed wheel. Swivel wheel. Locked wheel.

**620 DN.(12)72.(4)73****ACCESSORIES**

- (12)72: ISO DRAWERS 100 mm
- (4)73: ISO DRAWERS 200 mm