

631 DN.(2)60

DIMENSIONS 640 x 480 mm **HEIGHT** 1645 mm

MONOBLOC STRUCTURE

- Stainless steel AISI-304. Assembly with rivets and TIG welding.

UPPER - ISO PANELS

- Flexible organisation inside the trolley.
- Adjustable shelves, phenolic, for bulky material.

LOWER - ISO DRAWER FRAMEWORK

- Total opening.
- Steel ball-bearing slides with self-closing system.
- Front stop, it protects the slide against strong impacts when closing.
- Load capacity per drawer: 20 kg.
- Interior frame ISO 600 x 400 mm.

ISO DRAWERS 600 x 400 mm

- Heights 100, 200 mm. Interchangeable, ABS.
- ISO norm 3394.

2 DOORS

- Total opening 270°.
- Phenolic, 10 mm thickness.
- Lock with 4 keys.
- Card holder with white cards, removable, left door.
- DN Light grey.

VERTICAL HANDLES • 2 left side, 2 right side.

EXTENSIVE MOBILITY TROLLEYS

- Ø 125 mm wheels.
 - 2 antistatic, 2 with dual lock at the right side.
- Pedal position: Fixed wheel. Swivel wheel. Locked wheel.



631 DN.(2)60

ACCESSORIES

- (2)60: ADJUSTABLE SHELVES